



VHF AND UHF TRANSCEIVERS

IC-F3063T

(VHF transceiver with 10-keypad)

IC-F4063T

(UHF transceiver with 10-keypad)

IC-F3063S

(VHF transceiver without 10-keypad)

IC-F4063S

(UHF transceiver without 10-keypad)



F3063 F4063 Series



Icom Inc.

LTR[®]/Conventional/Digital* – Multi-Mode

* With UT-119H installed.



▲ IC-F3063T

▲ IC-F4063T

VHF TRANSCEIVERS

IC-F3063T

With 10-keypad

IC-F3063S

Without 10-keypad

UHF TRANSCEIVERS

IC-F4063T

With 10-keypad

IC-F4063S

Without 10-keypad

Basic LTR[®]/Conventional mixed mode operation

The IC-F3063 series provides LTR[®]/conventional mixed mode operation. Group, selective (DTMF), and phone call are available in LTR[®] mode.

IP54/55 Dust-protection and splash, water jet resistance

The IC-F3063 series meets IP54/55 requirements for dust-protection, splash and water jet resistance. Its durable construction is backed up by the aluminum die-cast chassis and polycarbonate casing, allowing reliable operation under harsh weather and environmental conditions.

Lithium-Ion battery pack

Supplied 2000mAh Li-Ion battery pack, BP-232, provides 14 hours* of operating time. Icom's rugged dual-rail guide securely locks the battery to the radio. Optional battery case BP-240 provides a convenient back up and great reassurance in an emergency.

* Typical operation Tx:Rx:Stand-by=5:5:90, power save on

Most popular signalings built-in

The IC-F3063 series has built-in 2-Tone, 5-Tone, CTCSS and DTCS signaling capabilities as standard for group communication or selective calling. Also, the IC-F3063 series can decode ten 2-Tone codes or eight 5-Tone codes on a channel. When a matched tone is received, the following actions are programmable for each code.

- Beep sound
- Bell icon
- Auto TX
- Answer back call
- Stun/kill radio
- Scan

Wide frequency range and large channel capacity

The IC-F3063 series covers a wide frequency range in one version (VHF 136–174 MHz, UHF 400–470MHz or 450–520 MHz). The 512 memory channel capacity with 128 zones allows you to divide and store a variety of flexible channel groupings. Memory channel selection can be made with a simple rotation of the rotary channel knob. Wide and narrow channel bandwidth (25/12.5kHz, 30/15kHz) is also programmable.

Land Mobile!

Full dot-matrix LCD

Using a large full dot-matrix LCD (32 × 18 mm), the IC-F3063 series shows upper and lower case characters clearly. The display setting is selectable from 1 line, 12 characters or 2 lines 24 characters via programming. The bottom row shows assigned functions to the [P0] to [P3] buttons.



Voting mode scanning

The Voting mode scanning detects the S-meter level of repeater stations and automatically selects the strongest station, useful for roaming between 2 or more repeater sites. In addition, the IC-F3063 series has 10 scanning modes including priority scan and double priority scan.

Enhanced audio

The IC-F3063 series employs a BTL amplifier that increases the audio output and the built-in audio compander provides clear, low noise communications.

Built-in inversion-type voice scrambler

The built-in inversion type voice scrambler provides secure conversation as standard. When a more secure system is required, the 32 code non-rolling-type voice scrambler UT-109R and 1020 code rolling type UT-110R are available as an option.

Other features

- BIIS 1200 compatible
- 8 DTMF autodial memories
- 2 step reduced power setting
- Power on password
- Busy, repeater lockout functions
- Radio stun and kill functions disable a lost or stolen unit over the air
- Surveillance function temporarily turns off the LED backlight and beep sound
- Powerful 5W output both VHF and UHF and more...

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACKS AND CASE



▲ BP-230 ▲ BP-231 ▲ BP-232 ▲ BP-240

Battery packs	Type and capacity	Operating time*	Output power
BP-230	Li-Ion 7.4V/ 800mAh	6 hours	5W
BP-231	Li-Ion 7.4V/1150mAh	8 hours	5W
BP-232	Li-Ion 7.4V/2000mAh	14 hours	5W
BP-240	AAA (LR03) batteries × 6	—	1W

* Operating time is approximate time (at 20°C). Tx: Rx: standby=5:5:90. Power save on.

REGULAR CHARGER



▲ BC-147 ▲ BC-171

BC-171 DESKTOP CHARGER + BC-147 AC ADAPTER
Charges the battery pack in 8–10 hours (approx.).

RAPID CHARGER



▲ BC-145 ▲ BC-160

BC-160 DESKTOP CHARGER + BC-145 AC ADAPTER
Charges the BP-232 in 3 hours (approx.).
BC-119N + AD-106 + BC-145 is also available.

POWER SUPPLY CABLES



▲ CP-17L ▲ OPC-515L

CP-17L CIGARETTE LIGHTER CABLE, OPC-515L DC POWER CABLE
For use with the BC-160 or BC-119N. (12–16V DC required).

MULTI-CHARGER



▲ BC-121N+AD-106 (6 pcs.) ▲ OPC-656 ▲ BC-157

BC-121N MULTI-CHARGER + AD-106 CHARGER ADAPTER + BC-157 AC ADAPTER
Rapidly charges up to 6 battery packs (Six AD-106s are required).
Charging time: 3 hours (approx.) when BP-232 is attached.

OPC-656 DC POWER CABLE :For use with the BC-121N. (12–20V DC required).

BELT CLIPS AND LEATHER BELT HANGERS



▲ MB-93 ▲ MB-96F

MB-93 : Swivel type belt clip.
MB-94 : Alligator type. Same as supplied.
MB-96N : Swivel type belt hanger.
MB-96F : Fixed type belt hanger.

HEADSETS and PTT/VOX UNIT



▲ HS-94 ▲ HS-95 ▲ HS-97 ▲ VS-15C

HS-94: Earhook headset with flexible boom microphone.
HS-95: Behind-the-head headset with flexible boom microphone.
HS-97: Throat microphone fits around your neck and picks up speech vibration.
VS-15C: PTT/VOX unit. Required when using these headsets with the transceiver.

SPEAKER-MICROPHONES



▲ HM-131SC ▲ HM-159SC

HM-131SC : Compact type speaker microphone.
HM-159SC : Full size durable speaker microphone with revolving clip.

INTERNAL UNITS



UT-109R VOICE SCRAMBLER UNIT UT-110R VOICE SCRAMBLER UNIT UT-119H DIGITAL UNIT

UT-109R: Up to 32 scrambling codes are available. 40-Pin type.
UT-110R: Up to 1020 scrambling codes are available. 40-Pin type.
UT-119H: Digital unit. Provides 6.25kHz digital capability.

EARPHONE



▲ AD-52 ▲ SP-13

SP-13 EARPHONE + AD-52 EARPHONE ADAPTER
Provides clear audio even in noisy environments.

STUBBY ANTENNAS



FA-SC56VS : 150–162MHz
FA-SC57VS : 160–174MHz
FA-SC73US : 450–490MHz
ANTENNAS
FA-SC25V : 136–150MHz
FA-SC55V : 150–174MHz
FA-SC25U : 400–430MHz
FA-SC57U : 430–470MHz
FA-SC72U : 470–520MHz

6.25kHz digital mode ready

DIGITAL

A first in the industry. With the optional UT-119H, the IC-F3063 series provides 6.25kHz digital narrow mode communication, and increases efficiency of channel allocation and use of spectrum. The IC-F3063 series provides 2 optional slots: one optional slot for the UT-119H digital unit and one for another option board.

This option may not be available in some countries. Please ask your dealer for details.



SPECIFICATIONS

GENERAL

- Frequency range :
IC-F3063T/S 136–174MHz
IC-F4063T/S 400–470MHz
450–520MHz
- Number of channels : 512 channels/128 zones
- Channel spacing : 12.5kHz/25kHz, 15kHz/30kHz,
6.25kHz (option)
- PLL channel step : 2.5kHz, 3.125kHz
- Antenna impedance : 50Ω
- Usable temperature range : –30°C to +60°C
- Power supply requirement : 7.2V DC
- Current drain (at 7.2V DC; approx.):
Transmit VHF/UHF 1.5A/1.8A (at 5W/5W)
Receive stand-by 95mA
rated output 600mA
- Dimensions (with BP-232) : 53 (W) × 136 (H) × 38.5 (D) mm
(projections are not included)
- Weight (approx.) : 340g (with BP-232)

TRANSMITTER

- Output power : 5W (VHF), 5W (UHF)
- Max. frequency deviation : ±5kHz (Wide)
±2.5kHz (Narrow)
- Frequency error : ±1.0ppm
- Spurious emissions : 75dB typ.
- Adjacent channel power : 80dB typ. (Wide), 70dB typ. (Narrow)
- FM Hum and Noise : 46dB typ. (Wide)
40dB typ. (Narrow)
- Audio harmonic distortion : 3% typ. (AF 1kHz, 40% deviation)
- Modulation limiting : 60–100% of max. deviation
- External microphone connector :
9-pin multi connector/ 2.2kΩ

All stated specifications are subject to change without notice or obligation.

LTR is a registered trademark of E.F. Johnson Company.
All other trademarks are the properties of their respective holders.

RECEIVER

- Intermediate frequency : 1st 46.35MHz
2nd 450kHz
- Sensitivity : 0.25μV typ. (at 12dB SINAD)
- Squelch sensitivity : 0.25μV typ. (at threshold)
- Adjacent channel selectivity : 75dB typ. (Wide)
68dB typ. (Narrow)
- Spurious response : 70dB min.
- Intermodulation : 74dB typ.
- Hum and noise ratio : 46dB typ. (Wide)
40dB typ. (Narrow)
- Audio output power : 500mW typ.
(at 5% distortion with an 8Ω load)
- External speaker connector: 9-pin multi connector/ 8Ω

SUPPLIED ACCESSORIES (May differ according to version)



Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan ☐ Phone: +81 (06) 6793 5302 ☐ Fax: +81 (06) 6793 0013

URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE, ☐
Bellevue, WA 98004, U.S.A. ☐
Phone ☐ +1 (425) 454-8155 ☐
Fax ☐ : +1 (425) 454-1509 ☐
E-mail ☐ sales@icomamerica.com ☐
URL ☐ : <http://www.icomamerica.com>

Icom Canada

Glenwood Centre #150-6165 Highway 17, ☐
Delta, B.C., V4K 5B8, Canada ☐
Phone ☐ +1 (604) 952-4266 ☐
Fax ☐ : +1 (604) 952-0090 ☐
E-mail ☐ info@icomcanada.com ☐
URL ☐ : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575 ☐
Unit 1 / 103 Garden Road, ☐
Clayton VIC 3168 Australia ☐
Phone ☐ +61 (03) 9549 7500 ☐
Fax ☐ : +61 (03) 9549 7505 ☐
E-mail ☐ sales@icom.net.au ☐
URL ☐ : <http://www.icom.net.au>

Icom New Zealand

146A Harris Road, East Tamaki, ☐
Auckland, New Zealand ☐
Phone ☐ +64 (09) 274 4062 ☐
Fax ☐ : +64 (09) 274 4708 ☐
E-mail ☐ inquiries@icom.co.nz ☐
URL ☐ : <http://www.icom.co.nz>

Icom (Europe) GmbH

Communication Equipment ☐
Himmelgeister Str. 100, ☐
D-40225 Düsseldorf, Germany ☐
Phone ☐ +49 (0211) 346047 ☐
Fax ☐ : +49 (0211) 333639 ☐
E-mail ☐ info@icom-europe.com ☐
URL ☐ : <http://www.icomeurope.com>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" ☐
08190, Sant Cugat del Valles, Barcelona, Spain ☐
Phone ☐ +34 (93) 590 26 70 ☐
Fax ☐ : +34 (93) 589 04 46 ☐
E-mail ☐ info@icomspain.com ☐
URL ☐ : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, ☐
Kent, CT6 8LD, U.K. ☐
Phone ☐ +44 (01227) 741741 ☐
Fax ☐ : +44 (01227) 741742 ☐
E-mail ☐ info@icomuk.co.uk ☐
URL ☐ : <http://www.icomuk.co.uk>

Icom France S.a

Zac de la Plaine, 1, ☐
Rue Brindejonc des Moulinais BP 5804, ☐
31505 Toulouse Cedex, France ☐
Phone ☐ +33 (5) 61 36 03 03 ☐
Fax ☐ : +33 (5) 61 36 03 00 ☐
E-mail ☐ info@icom-france.com ☐
URL ☐ : <http://www.icom-france.com>

Icom Polska

Sopot, 3 maja 54, Poland ☐
Phone ☐ +48 (58) 550 7135 ☐
Fax ☐ : +48 (58) 551 0484 ☐
E-mail ☐ icompolska@icompolska.com.pl ☐
URL ☐ : <http://www.icompolska.com.pl>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road, ☐
Taipei, Taiwan, R.O.C. ☐
Phone ☐ +886 (02) 2559 1899 ☐
Fax ☐ : +886 (02) 2559 1874 ☐
E-mail ☐ sales@asia-icom.com ☐
URL ☐ : <http://www.asia-icom.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding ☐
Road, Haidian District, Beijing, 100039, China ☐
Phone ☐ +86 (010) 5889 5391/5392/5393 ☐
Fax ☐ : +86 (010) 5889 5395 ☐
E-mail ☐ bjicom@bjicom.com ☐
URL ☐ : <http://www.bjicom.com>

Your local distributor/dealer: